

Avery Dennison™ Environmentally-Conscious Cable Ties

Fabricated with Avery Dennison's world-leading stretch technology, our environmentally-conscious cable ties are produced with up to 60% less material than standard cable ties of similar dimensions, yet have equal fastening strength. The cable ties enable manufacturers and retailers to reduce the weight and environmental impact of packaging materials, complying with government mandates and meeting their sustainability goals.

The cost-effective cable ties are available in Ladder Tie and Super Bar-Lok configurations, and can be made with natural, heat-stabilized, weather resistant or other materials. Avery Dennison's stretched ties are more resistant to moisture, environmental temperature extremes and ultra violet light than conventional ties, and have a high resistance to petrochemicals.

Ladder Ties

Avery Dennison Ladder Ties made with stretch technology consist of 60% less material than standard cable ties of the same length.

Key features and benefits

- High impact resistance and high tensile strength.
- Available in 7- and 11-inch lengths.
- Packaging weighs 22% less than standard cable tie packaging.
- Heat-stabilized from -40 F to 221 F (-40 C to 105 C).
- Non-corrosive and self-extinguishing (UL 94 Flam. Class V2 rating).

Super Bar-Lok Cable Ties

Ideally suited for marine and aviation applications, Avery Dennison Super Bar-Lok Cable Ties are produced with 37% less material than standard ties of the same length. The ties resist loosening and creep under long-term conditions of high heat, humidity and vibration.

Key features and benefits

- High impact resistance and high tensile strength.
- Resistant to cyclic shock fatigue, up to 70% longer than competitive ties.
- Heat-stabilized from -40 F to 221 F (-40 C to 105 C).
- Available in 7.5- and 15-inch lengths.
- Non-corrosive and self-extinguishing (UL 94 Flam. Class V2 rating).
- Military Specification Qualified (MS-3367).




Less material,
more environmentally-conscious
cable ties.

Avery Dennison™
Environmentally-Conscious Cable Ties

TOLERANCES: IN = ± .030 in
MM = ± 0.7 mm

TENSILE STRENGTH:	40 lbs. / 18.2 kg. MINIMUM PER MIL-S-23190.
MATERIAL:	NYLON 6/6 PER ASTM D4066, NATURAL
UL RECOGNIZED:	FILE NO. E57800
PACKAGED IN:	1000 PACKS IN SEALED BAGS (100 PACKS AVAILABLE)


STK. NO.	DESCRIPTION	DIM "A"	DIM "B"
08470	7' CABLE TIE, LADDER	5.75' / 6.30' 146mm / 160mm	7.0' / 8.0' 177.8mm / 203.2mm
08471	11', CABLE TIE, LADDER	10.60' / 10.90' 269.2mm / 276.9mm	11.00' / 12.00' 279.4mm / 304.8mm



TOLERANCES: IN = ± .030 in
MM = ± 0.7 mm

TENSILE STRENGTH:	50 lbs. / 22.8 kg. MINIMUM .
MATERIAL:	NYLON 6/6 PER ASTM D4066 - NATURAL TYPE I
UL RECOGNIZED:	FILE NO. E57800
APPLICATION TOOL:	TOOL, HAND ADJUSTABLE, FOR PLASTIC TIE DOWN STRAP. AVERY DENNISON PART NUMBER 12001.
TOOL TENSION SETTING:	6-8

STK. NO.	DESCRIPTION	MILITARY SPEC.	DIM "A"	DIM "B"	BUNDLE DIA.	PACKAGED IN *
10001	7.5' SUPER BAR-LOK® CABLE TIE, STANDARD	MS3367-1-9	6.0' ±.25 152.4mm ±6.4mm	8.0' ±.25 203.2mm ±6.4mm	1/16" - 1-3/4"	1000/BAG 5000/CASE
10344	15' SUPER BAR-LOK® CABLE TIE, STANDARD	MS3367-2-9	13.6' ±.25' 345.4mm ±6.4mm	16.0' ±.50' 406.4mm ±12.7mm	1/16" - 4"	500/BAG 5000/CASE



About Avery Dennison

Avery Dennison is committed to product innovation, service excellence and maintaining the highest quality standards to exceed our customers' expectations. Standards include: Quality Management--ISO/TS16949, Environmental--ISO14001, Health and Safety--OHAS18000. With over 30 year's experience in product development and innovation, Avery Dennison can design environmentally-conscious cable ties that meet your specific needs.



www.fastener.averydennison.com

Americas
Avery Dennison Corporation
Fastener
224 Industrial Road
Fitchburg, MA 01420
Tel: 800-225-5913
Fax: 800-848-2169
Email: fastener.usa@averydennison.com

Asia
Avery Dennison Corporation Fastener
2/F 33 Chun Choi Street
Yan Hing Industrial Building
Tseung Kwan O Industrial Estate
New Territories
Hong Kong
Tel: 852-2555-9441
Fax: 852-2873-6436
Email: info_fap@ap.averydennison.com

Europe, Middle East and Africa
Avery Dennison UK Ltd.
Unit 1, Thomas Road
Wooburn Industrial Park
Wooburn Green
Bucks HP10 0PE
United Kingdom
Tel: 44 (0) 1628 859530
Fax: 44 (0) 1628 859567
Email: fast.info@eu.averydennison.com