


AVERY DENNISON MARKETING SPECIFICATION

HISTORY

REV.	DATE	DESCRIPTION
D	2NOV12	UPDATED FILE FORMAT & MATCH PRINT TO PART

THE SUBJECT MATTER DISCLOSED HEREIN EMBODIES PROPRIETARY INFORMATION WHICH IS THE CONFIDENTIAL PROPERTY OF THE AVERY DENNISON CO. NONE OF WHICH SHALL BE COPIED, REPRODUCED, DISCLOSED TO OTHERS, PUBLISHED OR USED IN WHOLE OR IN PART, FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS BEING MADE AVAILABLE WITHOUT THE EXPRESS ADVANCE WRITTEN PERMISSION OF A DULY AUTHORIZED AGENT OF THE COMPANY. THIS DOCUMENT IS THE PROPERTY OF THE AVERY DENNISON CO. AND IS TO BE RETURNED TO THE COMPANY ON DEMAND.



MOUNTING:	M8 STUD
TENSILE STRENGTH:	50 LBF / 222.4N MIN.
OPERATING TEMP RANGE:	-40°F (-40°C) TO 257°F (125°C)
WEIGHT:	1.7 GRAMS EACH
BUNDLE DIAMETER:	$\varnothing 1/4"$ (6.35MM) TO $\varnothing 1-3/4"$ (44.5MM)
INSTALLATION TOOL:	12001 - HAND TOOL 12500 - PNEUMATIC TOOL
TOOL TENSION SETTING:	6 - 8
PACKAGING:	1000/BAG, 5 BAGS/MASTER

APPROVALS:

ENG. APPR. *[Signature]* 2 Nov 12

Q.A. APPR. *[Signature]* 11/02/2012

SPECIFIED TOLERANCES	
INCHES	(MM)
.XX ± .03	.X ± .7
.XXX ± .01	.XX ± .25
ANGULAR: ± 2°	

MATERIAL	IMPACT MODIFIED HEAT STABILIZED NYLON 6/6
COLOR	GRAY

AVERY DENNISON

FASTENER DIVISION
FITCHBURG, MA 01420 U.S.A.
TEL. 1-800-225-5913
FAX. 978-353-8157

DESCRIPTION	M8 MOUNT 7.5" CABLE TIE	
STOCK NO.	20044-0	REV.
		D